






Customer Details

Height: _____ Weight: _____ Age: _____ Patient Name _____

Sling Types & Size (specialty slings cost extra)

*please note slings are non-returnable unless unused & in their original condition

<p>Standard</p>  <p>XS S M L XL</p>	<p>Double Amputee</p>  <p>S M L (Upcharge)</p>	<p>Net/Mesh</p>  <p>S M L (Upcharge)</p>	<p>Fleece Lined</p>  <p>M L (Upcharge)</p>	<p>Head-Supported</p>  <p>S M L (Upcharge)</p>
--	---	---	--	---

Sling Size Guide

		HEIGHT																
height in ft.		3ft	3ft 3in	3ft 6in	3ft 9in	4ft	4ft 3in	4ft 6in	4ft 9in	5ft	5ft 3in	5ft 6in	5ft 9in	6ft	6ft 3in	6ft 6in	6ft 9in	
weight in lbs.		X SMALL			SMALL				MEDIUM				LARGE			X LARGE		
56																		
63																		
70																		
77																		
84																		
91																		
98																		
105																		
112																		
119																		
126																		
133																		
140																		
147																		
154																		
161																		
168																		
175																		
182																		
189																		
196																		
203																		
210																		
217																		
224																		
231																		
238																		
245																		
252																		
259																		
266																		
273																		
280																		
287																		
294																		
301																		
308																		
315																		
322																		


*Max weight capacity is 330lbs

MILFORD ASSESSMENT FORM

Vehicle Details

Make: _____ Model: _____ Year: _____

Installation Position:



Passenger Side = Front Right Side
 Rear Passenger Side = Rear Right Side
 Side Rear Driver Side = Rear Left Side

Please provide the four measurements **(in inches)** below:

A: From the ground to the top of the sill.

B: From the ground to the depression in seat.

X: From the ground to the top of wheelchair seat.


Y: From the ground to the middle of sternum - **Seated as upright as possible for accuracy**




A = _____



B = _____



X = _____



Y = _____


Sill Bracket

Sill Brackets are used on vehicles that have a low dash or to retain the use of the glovebox. This is typically used in smaller vehicles and will need to be removed before closing the vehicle door.

***Using a Sill Bracket will reduce the weight capacity by 55lbs., minimize foot/leg space & can not be used with vehicle specific applications (unless designed in conjunction)**

Does the vehicle need a Sill Bracket?

Yes _____ No _____



MILFORD ASSESSMENT FORM

Other Options & Accessories

Spreader Bar



A Spreader Bar is included with your Milford Order

Sm (11.25") _____ Med (13.5") _____ Lg (17.5") _____

The Spreader Bar should be at chest height when lifting the client. In some cases, a protective padded cover may be appropriate for the client.

Spreader Bar Covers are additional cost

Spreader Bar Cover: Yes _____ No _____